Oakland Fire Department Fire Prevention Bureau 250 Frank H. Ogawa Plaza, Ste 3341 Oakland, CA 94612 510-238-3851



Report of Fire Inspection Commercial Inspection



For Official Use Only Start Time: 1945 End Time: 500 O/C BTL# 10 34383 E/C# 25 St. 4 TJT ...S

Address: 4/2	Monitori , Ste Business Name: Commences Merals	
Contact Name:	and the state of t	(#
Inspection:		CTT TOURS LAND
	Inspection Permission Granted: □Yes □ No	
the control of the co		N/C OK N/A
and the second s	ETY REQUIREMENTS	
CFC 505.1	Provide building address numbers plainly visible and legible from the street or road fronting the property.	
CFC 304.3.3	Keep dumpsters 5 feet from combustible walls, openings, and combustible roof eaves.	
CFC 3404.3.4.4	Reduce the amount of flammable or combustible liquids used for maintenance purposes for the operation of equipment to 10 gallons or less.	
CFC 315.2.3 CFC 315.2.1	Combustible not permitted in boiler rooms, mechanical rooms, or electrical equipment rooms. Storage shall be maintained 2 ft. or more below the ceiling in non-sprinkled areas of the buildings or a minimum of 18" below sprinkler deflectors.	
CFC 315.2	Storage of combustible materials in buildings shall be orderly with storage separated from heating devices.	
CFC 304.3.1	Materials susceptible to spontaneous ignition, such as oily rags, shall be stored in a listed disposal container.	
CFC 506.2	Fire Department key box (Knox box) is installed and keys are current.	
CFC 503.4	Fire access roads shall not be obstructed in any manner.	
CFC 703.1 #2	Repair, restore or replaced damaged, altered, or breached all penetrations to fire-resistive rated construction.	
EXITING SAFE	TY REQUIREMENTS	
CFC 1001.2	Remove obstructions from exits, aisles, corridors, and stairways.	
CFC 1008.1.9.3	Locking devices shall be approved.	
CFC 703.2	Exit doors shall be maintained in operable condition, at all times.	
CFC 1008.1.2	Exit doors shall swing in the direction of travel when occupant load exceeds 50 persons.	
CFC 1008.1.9.3	Provide sign "DOOR TO REMAIN UNLOCKED WHILE OCCUPIED" above main entrance.	
CFC 1011.2	Provide illuminated (internal/external powered) exit signs when two or more exits are required.	
CFC 1011.1	Exit signs shall be installed at required exits and where otherwise necessary to clearly indicate direction of egress.	
CFC 1006.1	Provide illuminated means of egress whenever building is occupied.	
CFC 1006.3 CFC 1014.4.1	Provide/Service emergency egress illumination when two or more exits are required. Minimum clear aisle width shall not be less than 36 inches.	
FIRE PROTECT CFC 906.1	A minimum of one 2A:10B:C fire extinguisher present for each 3000 sq/ft, travel distance not to exceed 75 ft.	
CFC 906.1	Service fire extinguishers annually, or when gauge indicates service required.	
CFC 906.1 #2		
	Install a 40-B:C fire extinguisher within 30 feet of cooking equipment and a Class K fire extinguisher for deep fat fryers.	
CFC 907.20.1 19 CCR § 904	Fire Alarm shall be maintained in operating condition. Fire Suppression systems shall be in operating condition (Inspected/Serviced Qtrly; Recertified every 5 years).	
CFC 903.4	Sprinkler systems with 20 heads or more shall be electronically supervised.	
	Commercial cooking equipment producing grease laden vapors shall be provided with an automatic fire extinguishing	
CFC 904,11	system.	
CFC 508.5.4 CFC 904.11.6.4	Fire hydrants and other fire protection equipment shall not be obstructed. Service automatic fire-extinguishing systems every 6 months, and after activation of the system.	
CFC 605.5	EQUIREMENTS Extension cords and flexible cords shall not be used as a substitute for permanent wiring.	
CFC 605.5.3	Appliance cords maintained in good condition without splices, deterioration, or damage.	
CFC 605.3	Provide a minimum clearance of 30" wide, 36" deep, and 78" from face of electrical switchboards and panel boards. Clearly identify electrical rooms with signage and label all disconnecting means, feeder/branch circuits.	
CFC 605.3.1 CFC 605.6	Open junction boxes and open-wiring splices shall be provided with approved electrical outlet/switch covers.	
PERMITS	Open junction doxes and open-witing spinors shall be provided with approved electrical cancer with a covers.	
105.6.34	Obtain Public Assembly Permit from Fire Prevention	
105.6.32	Obtain Open Flame Permit for Candles/Open flame in Public Assembly occupancies from Fire Prevention	
105.6.22	Obtain Permit for High-Piled Storage	
· · · · · · · · · · · · · · · · · · ·	OUS REQUIREMENTS	
OMC 5.04.040	Valid City of Oakland Business Tax Certificate	
CCR 2729.1(a)	Provide/Obtain a current Hazardous Materials Business Plan (HMBP)	
In accordance with the California Fire Code Section 104.5 you are hereby ordered to correct all violations marked N/C immediately upon receipt of this notice. Failure to comply with this lawful order may result in a citation to appear in Municipal Court, plus additional fees and civil penalties. An inspection to determine if you have complied with this order will be conducted on or about/ An inspection fee will be invoiced at a later date in accordance with the City's Master Fee Schedule. If you have questions, contact the inspector above at phone number Date:		
Date:/_	Owner/wigi (Signature) Owner/wigi, (Finit)	