Oakland Fire Department Fire Prevention Bureau 250 Frank H. Ogawa Plaza, Ste 3341 Oakland. CA 94612

Report of Fire Inspection

_	-	
٩	KLANO	
A		
оно	1601	
1	A P	
Die	DELLA	

Fa	r Official	Use	Only

Start Time:	End Time:	
Occupancy	BTL#	

	nd, CA 94612 0-238-3851 Map - Block 4	2-4404	TJT
Inspection:	Inspection Date: ZIII		
	and rank of person conducting inspection C+ PCXC Apparatus:	EZT	
Address:			, Ste
Business Name	e: Taricabbagot Business Conducted Tany wo	MARIA	'Zn
Contact Name:	Port of Ocean Owner/Mgr Phone # 510/4632440 Business Pl	hone	•
Mailing Addre			
_	with Responsible Person/Inspection Permission Granted Yes No		· · · · · · · · · · · · · · · · · · ·
	ETY REQUIREMENTS	N/C OK	N/A
CFC 505.1	Provide building address numbers plainly visible and legible from the street or road fronting the property.		
CFC 304.3.3	Keep dumpsters 5 feet from combustible walls, openings, and combustible roof eaves.		
CFC 3404.3.4.4	Reduce the amount of flammable or combustible liquids used for maintenance purposes for the operation of equipment to 10 gallons or less.		
CFC 315.2.3	Storage not permitted in boiler rooms, mechanical rooms, or electrical equipment rooms.		
CFC 315.2.1	Storage shall be maintained 2 ft. or more below the ceiling in non-sprinkled areas of the buildings or a minimum of 18" below sprinkler deflectors.		
CFC 315.2	Storage of combustible materials in buildings shall be orderly with storage separated from heating devices.		
CFC 304.3.1	Materials susceptible to spontaneous ignition, such as oily rags, shall be stored in a listed disposal container.		
CFC 506.2	Fire Department key box (Knox box) is installed and keys are current.		
CFC 503.4	Fire access roads shall not be obstructed in any manner.		
CFC 703.1 #2	Repair, restore or replaced damaged, altered, or breached all penetrations to fire-resistive rated construction.		لسا
EXITING SAFE: CFC 1001.2	I'Y REQUIREMENTS Remove obstructions from exits, aisles, corridors, and stairways.		
CFC 1008.1.9.3	Exit doors for Occ> 10 shall be openable from the egress side without the use of a key or special knowledge or effort.	H H	
CFC 703.2	Exit doors shall be maintained in operable condition, at all times.	<u> </u>	_=
CFC 1008.1.2	Exit doors shall swing in the direction of travel when occupant load exceeds 50 persons.		
CFC 1008.1.9.3	Provide sign "DOOR TO REMAIN UNLOCKED WHILE OCCUPIED" above main entrance.		
CFC 1011.2	Provide illuminated (internal/external powered) exit signs when two or more exits are required.		. 🖳
CFC 1011.1 CFC 1006.1	Exit signs shall be installed at required exits and where otherwise necessary to clearly indicate direction of egress. Provide illuminated means of egress whenever building is occupied.		<u></u>
CFC 1006.1	Provide/Service emergency egress illumination when two or more exits are required.		
CFC 1014.4.1	Minimum clear aisle width shall not be less than 36 inches.	占 街	
FIRE PROTECT	ION SYSTEMS		
CFC 906.1 CFC 906.2	A minimum of one 2A:10B:C fire extinguisher present for each 3000 sq/ft, travel distance not to exceed 75 ft. Service fire extinguishers annually, or when gauge indicates service required.		
CFC 906.1 #2	Install a 40-B:C fire extinguisher within 30 feet of cooking equipment and a Class K fire extinguisher for deep fat fryers.		
CFC 907.20.1	Fire Alarm shall be maintained in operating condition.		
19 CCR § 904	Fire Suppression systems (Sprinklers) shall be in operating condition (Inspected/Serviced Qtrly; Recertified every 5 years).		
CFC 903.4	Sprinkler systems with 20 heads or more shall be electronically supervised.		
CFC 904.11	Commercial cooking equipment producing grease laden vapors shall be provided with an automatic fire extinguishing system.		
CFC 904.11.6.4 CFC 508.5.4	Service automatic fire-extinguishing systems every 6 months, and after activation of the system. Fire hydrants and other fire protection equipment shall not be obstructed. FDC, Sprinkler Connections, PIV's and other Shutoffs maintained in an operable condition.		
CFC 912.3 ELECTRICAL E	REQUIREMENTS		
CFC 605.5	Extension cords and flexible cords shall not be used as a substitute for permanent wiring.	\vdash	
CFC 605.5.3	Appliance cords maintained in good condition without splices, deterioration, or damage.	= =	
CFC 605.3	Provide a minimum clearance of 30" wide, 36" deep, and 78" from face of electrical switchboards and panel boards.	/	
CFC 605.3.1	Clearly identify electrical rooms with signage and label all disconnecting means, feeder/branch circuits.		
CFC 605.6	Open junction boxes and open-wiring splices shall be provided with approved electrical outlet/switch covers.		
PERMITS			
105.6.22	Obtain Permit for High-Piled Storage – Storage greater than 12 feet high		
	DUS REQUIREMENTS		
OMC 5.04.040	Valid City of Oakland Business Tax Certificate	لــا لــا	٠.
Notes	Loase get Gre extinguisher		· · · · · · · · · · · · · · · · · · ·
·			

Edward Hamilton

3 Acra A Vantta